

# POWERTEX

Rinforzante alcalino per l'utilizzo in lavatrici professionali

POWERTEX è un eccezionale booster di lavaggio da abbinare ad un detergente della gamma Pulitissimo. Esercita un'azione energica contro lo sporco grasso e l'unto ed ha un'elevata capacità di rimozione delle macchie anche in presenza di acque dure. Adatto per qualsiasi tipologia di tessuto (ad eccezione dei delicati), POWERTEX è compatibile con qualsiasi tipo di macchina lavabiancheria.

*Prodotto per uso professionale.*

### Caratteristiche chimico fisiche

<b>Aspetto fisico</b>	Liquido limpido
<b>Colore</b>	Paglierino
<b>Odore</b>	Caratteristico
<b>Densità a 20 °C</b>	ca. 1,25 g/mL
<b>pH (tal quale)</b>	ca. 13

*I dati sopra riportati sono valori tipici di produzione e non costituiscono specifica.*

### Modalità d'impiego

POWERTEX può essere utilizzato per qualsiasi tipologia di tessuto in cotone e poliestere ad eccezione dei capi delicati. Temperatura di lavaggio consigliata: 30 – 90°C. POWERTEX è appositamente formulato per utilizzo con sistemi di dosaggio automatico.

Aggiungere in fase di prelavaggio e/o lavaggio da 3 a 20 ml/Kg di POWERTEX in base al livello di sporco e alla durezza dell'acqua come riportato nella tabella.

Dosaggio consigliato in g per Kg di biancheria asciutta:

	Durezza dell'acqua in gradi francesi (°F)		
	Dolce (0-15°F)	Media (15-25°F)	Dura (Oltre 25°F)
Pre lavaggio	3	6	8
Lavaggio	8	12	16
Bagno Unico	10	14	20



### Conservazione

Conservare a temperature comprese tra 5°C e i 40°C. Il prodotto conservato correttamente nei contenitori originali mantiene inalterate le sue caratteristiche per 24 mesi.

### Informazioni sull'immagazzinamento

Evitare l'uso improprio del prodotto. Conservare negli imballi originali chiusi o, dove applicabile, negli appositi locali o serbatoi di stoccaggio lontano da temperature estreme e lontano dalla luce del sole diretta. Tenere lontano da cibi, bevande e mangimi.

Per informazioni relative alla manipolazione e allo smaltimento delle soluzioni consultare la scheda di sicurezza.

I.R.C.A. SERVICE S.p.A. non è responsabile in alcun caso per l'utilizzo improprio del prodotto.

### Confezioni disponibili:

Codice	Collo	N. Conf. Strati	N. Strati Pallet	N. Conf. Pallet
60016036	Tanica Kg.25	13	2	26

### I.R.C.A. SERVICE S.p.A.

Strada Statale Cremasca 591 n° 10  
24040 Fornovo San Giovanni (BG)  
Tel. 0363 337250 – Fax 0363 337251  
e-mail: [info@ircaservice.com](mailto:info@ircaservice.com)  
[www.ircaservice.com](http://www.ircaservice.com)



# POWERTEX

Alkaline strengthener for use in professional washing machines

POWERTEX is an exceptional washing booster in combination with a detergent from the Pulitissimo range. It exerts a powerful action against greasy dirt and grease and has a high stain removal capacity even in the presence of hard water. Suitable for all types of fabric (except delicates), POWERTEX is compatible with any type of washing machine.

*Product for professional use.*

## Physical and chemical properties

<b>Physical appearance</b>	Clear liquid
<b>Colour</b>	Straw yellow
<b>Odour</b>	Typical
<b>Density at 20 °C</b>	approx. 1.25 g/ml
<b>pH (as is)</b>	approx. 13

*The aforementioned data refer to typical production values and do not constitute a specific example.*

## Directions

POWERTEX can be used for all types of cotton and polyester fabrics with the exception of delicate garments. Recommended washing temperature: 30 – 90°C. POWERTEX is specially formulated for use with automatic dosing systems.

Add 3 to 20 ml/Kg of POWERTEX to the prewash and/or wash depending on the level of dirt and water hardness as shown in the table.

Recommended dosage in g per kg of dry linen:

	Water hardness in French degrees (°F)		
	Soft (0-15°F)	Medium (15-25°F)	Hard (over 25°F)
Pre-wash	3	6	8
Wash	8	12	16
Single Bath	10	14	20





# TECHNICAL DATA SHEET

## Storage

Store at temperatures between 5°C and 40°C. If properly stored in original containers, the product will keep its characteristics unchanged for 24 months.

## Storage information

Avoid misuse of the product. Store in original sealed packages or, where applicable, in special places or storage tanks away from extreme temperatures and keep away from direct sunlight. Keep away from food, drink and animal feed.

Refer to the Safety Data Sheet for information on handling and the disposal of solutions.

I.R.C.A. SERVICE S.p.A. is not liable for any misuse of the product.

## Available packaging:

Code	Package	Pack. No. Layers	Pallet Layer No.	Pack. No. Pallet
60016036	Tank 25Kg	13	2	26

## I.R.C.A. SERVICE S.p.A.

Strada Statale Cremasca 591 n°10  
24040 Fornovo San Giovanni (BG)  
Tel. 0363 337250 – Fax 0363 337251  
e-mail: [info@ircaservice.com](mailto:info@ircaservice.com)  
[www.ircaservice.com](http://www.ircaservice.com)

